EVERSTEIN

USER MANUAL

BATH MIXING PROGRAM
PROGRAMA MEZCLADORES BAÑO
PROGRAMME DU MITIGEUR POUR LA SALLE DE BAIN

SFS1036

Website: www.everstein.com
Phone: +1-888-666-8220
Email: info@everstein.com

Warranty Duration

All components of this faucet system are covered under a lifetime limited warranty, ensuring they are free from defects in material and workmanship for the original purchaser.

Repair and Replacement

If the product shows defects in material or workmanship under normal use and within the warranty period, we will, at our discretion, either repair the product or provide a replacement at no cost to the original purchaser. Please note that proof of purchase (e.g., an invoice) is required when requesting service. The warranty does not cover damages caused by improper installation, misuse, or modifications.

Exclusions

We shall not be responsible for the following cases:

- Damage to the product caused by improper installation, misuse, unauthorized repair or replacement, or abuse (including damage during shipment).
- Damage to the product caused by improper dismantling after installation.
- Damage resulting from abnormal water pressure or impurities in water pipes, which is not covered under this warranty.
- Rust on the product due to insufficient care and maintenance, which is not covered under this warranty.
- Damage caused by natural disasters such as fire, flood, earthquake, lightning storms, etc., which is not covered under this warranty.

I hope this helps! If you have any further questions or concerns,please let me know.

Having Trouble?Contact us.

Email: info@everstein.com

Phone: +1-888-666-8220

EVERSTEIN



M6396-10
SFS-1036

CONTENT


Balance Shower Faucet Installation Manual ---------- **(1-7)**


CONTENIDO

Manual de Instalación del Grifo de Ducha de Balance ---------- **(8-14)**

Installation and Maintenance Matters









1. Check the accessories list to verify that all parts are complete in this package.
2. Do not disassemble the main body by yourself.
3. Connect inlet pipes to supply valves.
4. Make sure inlet pipes and supply valves have no impurities and are cleaned, with no impurities in the pipeline.
5. After installation, check all joints for leakages.
6. Do not leave the rain shower system exposed to a severely corrosive environment.

Do's

1. In order to keep the mixer surface bright, please clean the mixer regularly.
2. Rinse the faucet with clean water and wipe it with a soft cotton cloth.
3. Use one of the following cleaners to remove dirt from the surface:

a. Mild liquid cleaner.

b. Colorless glass cleaner and powder cleaner that do not cause abrasion and can be dissolved completely.

c. Polish liquid that does not cause abrasion.


Don'ts

1. Avoid using cleaning powder, harsh cleaning chemicals, brushes and coarse cloth to prevent scratching and friction.
2. Do not use acid cleaners to clean the faucet as they may cause surface corrosion of the faucet. If the faucet is exposed to harmful acid substances, please rinse it immediately with water.

Tools Needed:




2-Function Rain Shower Faucet Set
Accessories List




No.	Part name	Qty	No.	Part name	Qty
1	Shower head	1	10	Lifting rod	1
2	Shower arm	1	11	Connector	1
3	Shower arm cup	1	12	Cup	1
4	Main body	1	13	Main body spare parts	4
5	Deck plate	1	14	Instruction manual	1
6	Handle	1	15	Gloves	2
7	Handle cap	1	16	Handle wrench	1
8	Shower hand	1	17	Lifting rod parts	1set
9	Shower hose	1			

◆ Essential Dimensions & Water Pipe Lines

Unit: mm/inch




◆ Installation Depth of the Connector and Shower Arm



The thickness of the tile must be calculated for installation.
Connector size of male thread: USA: 1/2"-14NPT, Canada: 1/2"-14NPT, Europe: G1/2".


◆ Installation Depth of the Main Body



Notice: 1. The installation depth of the main body should be no less than 2 3/16" (55mm) and no more than 3 1/8" (80mm), including the thickness of the tile. Otherwise, the deck plate cannot be installed.

2. The opening size of ceramic tile shall be smaller than the deck plate size.

◆ Piping Instructions before Tiling




1.As shown in the figure, the inlet and outlet pipes are pre-buried. Please pay attention to the correct direction when installing the pre-buried main body.


2.Before tiling, turn on the water to test whether the left and right inlet pipes are tightly connected without leakage.Then, adjust the flow switch to the "on" position to check for leaks in the mixed outlet pipes.

◆ Main Body Valve Installation

Step1




(Concrete wall)



(wood wall)

1.Make marks according to the size of the main body valve, and then drill anchors into the wall (concrete wall).
2.Lock the main body to wood directly with screws (wood wall).
3.When installing the main body, please mark the UP side up and do not install it upside down.
▲ Please note that the level meter should be parallel to the wall; otherwise, the deck plate cannot be installed.


Step2



Do not remove the white wear ring; otherwise, the handwheel will be damaged.




Attention:Please adjust the constant temperature baffle plate to the lower part when you areinstalling the handle





Precautions for handwheel installation


1.Use Main body spare parts and to fixed Main body on the wall and then install deck plate.
2.Please fix the main body to the wall install deck plate ,water diverter screw and water diverter cap step by step.
3.Install the handle with the screw and handle cap.


Slide Bar Installation















Step 1: Mark the punch position with a pen, drill holes using a 6 mm electric drill.
Step 2: Then knock the plastic anchors in.
Step 3: Place the base and fasten with mounting screws.
Step 4: Install the shower vertical bar into the base.
Step 5: Fully tighten the set screw. Installation completed.
Step 6:
1.Wrap the connector with Teflon tape. Screw the thread into the water pipe inside the wall.
2.Install the rubber pad on the shower hose and connect it to the connector.

◆ Shower Head Installation




1. Connect shower arm with the cover before screwing arm into riser connection to prevent damage.
2. Fix shower head onto shower arm and apply tape to pipe threads on both ends.
3. Do not over tighten shower head. It is 360° swivel connection.

VERSTEIN

◆ Instalación y Cuestiones de Mantenimiento









1. Verifique la lista de accesorios para comprobar que todas las partes están completas en este paquete.
2. No desmonte el cuerpo principal por sí mismo.
3. Conecte las tuberías de entrada a las válvulas de suministro.
4. Asegúrese de que las tuberías de entrada y las válvulas de suministro no tengan impurezas y estén limpias, sin impurezas en la tubería.
5. Después de la instalación, verifique todas las uniones para detectar fugas.
6. No deje el sistema de ducha tipo lluvia expuesto a un entorno altamente corrosivo.

Hacer

1. En para mantener la superficie de la batidora brillante, limpie el mezclador regularmente.
2. Inse el grifo con agua limpia y límpielo con un suave ropa de algodón.
3. Utilice uno de los siguientes limpiadores para eliminar la suciedad de la superficie:
   a. Limpiador líquido suave.
   b. Limpiador de vidrio incoloro y limpiador en polvo que no causen abrasión y que se puedan disolver completamente.
   c. Líquido pulidor que no cause abrasión.


No hacer

1. Valte con polvo de limpieza, productos químicos de limpieza duros, cepillos y tela gruesa para evitar rascar y fricción.
2. No use limpiadores de ácidos para limpiar el grifo, ya que pueden causar corrosión superficial del grifo. Si el grifo está expuesto a sustancias ácidas dañinas, enjuague inmediatamente con agua.

Herramientas Necesarias:




◆ Juego de Grifo de Ducha de Lluvia de 2 Funciones
Lista de Accesorios




N.°	Nombre de la pieza	Cant.	N.°	Nombre de la pieza	Cant.
1	Cabezal de ducha	1	10	Barra de elevación	1
2	Brazo de ducha	1	11	Conector	1
3	Copa del brazo de ducha	1	12	Taza	1
4	Cuerpo principal	1	13	Piezas de repuesto del cuerpo principal	4
5	Placa de cubierta	1	14	Manual de instrucciones	1
6	Manija	1	15	Guantes	2
7	Tapa de la manija	1	16	Llave de manija	1
8	Ducha de mano	1	17	Piezas de la barra de elevación	1 juego
9	Manguera de ducha	1	18		

◆ Dimensiones Esenciales y Líneas de Tubería de Agua




◆ Profundidad de Instalación del Conector y Brazo de Ducha




El grosor del azulejo debe ser calculado para la instalación.
Tamaño del conector de rosca macho: EE. UU.: 1/2"-14NPT, Canadá: 1/2"-14NPT, Europa: G1/2".

◆ Profundidad de Instalación del Cuerpo Principal



Aviso: 1. La profundidad de instalación del cuerpo principal no debe ser inferior a 2 3/16" (55 mm) y no más de 3 1/8" (80 mm), incluyendo el grosor del azulejo. De lo contrario, la placa de cubierta no podrá ser instalada.
2. El tamaño de apertura del azulejo cerámico debe ser menor que el tamaño de la placa de cubierta.


◆ Instrucciones de Tuberías antes del Alicatado




1.Como se muestra en la figura, las tuberías de entrada y salida están pre-enterradas. Por favor, preste atención a la dirección correcta al instalar el cuerpo principal pre-enterrado.
2.Antes de colocar los azulejos, abra el agua para probar si las tuberías de entrada izquierda y derecha están conectadas herméticamente sin fugas. Luego, ajuste el interruptor de flujo a la posición "on" para comprobar si hay fugas en las tuberías de salida mezcladas.

◆ Instalación de la Válvula del Cuerpo Principal

Paso 1



(Pared de concreto)




(pared de madera)

1. Marque según el tamaño de la válvula del cuerpo principal y luego perfore para colocar los anclajes en la pared (pared de concreto).
2. Fije directamente el cuerpo principal a la madera con tornillos (pared de madera).
3. Al instalar el cuerpo principal, por favor marque el lado UP hacia arriba y no lo instale al revés.

▲ Tenga en cuenta que el nivel debe estar paralelo a la pared; de lo contrario, la placa de cubierta no podrá ser instalada.


Paso 2



No retire el anillo blanco de desgaste; de lo contrario, la rueda manual se dañará.




Atención: ajuste la placa deflectora de temperatura constante a la parte inferior cuando esté instalando la manija.





Precauciones para la instalación de la rueda manual


1. Use las piezas de repuesto del cuerpo principal para fijar el cuerpo principal en la pared y luego instale la placa de cubierta.
2. Por favor, fije el cuerpo principal a la pared e instale la placa de cubierta, el tornillo del desviador de agua y la tapa del desviador de agua paso a paso.
3. Instale la manija con el tornillo y la tapa de la manija.


Instalación de la Barra Deslizante














Paso 1: Marque la posición de perforación con un lápiz, taladre agujeros con un taladro eléctrico de 6 mm.
Paso 2: Inserte los tacos de plástico golpeándolos suavemente.
Paso 3: Coloque la base y atornille los tornillos de fijación.
Paso 4: Instale la barra vertical de la ducha en la base.
Paso 5: Apriete completamente el tornillo de fijación. Instalación completada.
Paso 6:
1.Envuelva el conector con cinta de teflón y atornille la rosca en la tubería de agua empotrada en la pared.
2.Coloque la arandela de goma en la manguera de ducha y conéctela al conector.

◆ Instalación del Cabezal de Ducha



1. Conecte el brazo de la ducha con la cubierta antes de atornillar el brazo en la conexión del elevador para evitar daños.
2. Fije el cabezal de ducha al brazo de ducha y aplique cinta a las roscas de la tubería en ambos extremos.
3. No apriete demasiado el cabezal de ducha. Es una conexión giratoria de 360°.

EVERSTEIN

Website: www.everstein.com
Phone: +1-888-666-8220
Email: info@everstein.com